



SPECIFICATIONS
 Current Rating: 1A AC,DC
 Voltage Rating: 150V AC,DC
 Temperature Range: -25°C ~ +85°C
 Contact Resistance: 30mΩ Max.
 Insulation Resistance: 500MΩ Min.
 Withstanding Voltage: 500V AC/minute
 Material: Nylon 66,UL94V-0
 Pantone color: 7529C

Circuit No.	Dimensions		
	A	B	C
02P	1.25	4.25	2.75
03P	2.50	5.50	4.00
04P	3.75	6.75	5.25
05P	5.00	8.00	6.50
06P	6.25	9.25	7.75
07P	7.50	10.50	9.00
08P	8.75	11.75	10.25
09P	10.00	13.00	11.50
10P	11.25	14.25	12.75
11P	12.50	15.50	14.00
12P	13.75	16.75	15.25
13P	15.00	18.00	16.50
14P	16.25	19.25	17.75
15P	17.50	20.50	19.00
20P	23.75	26.75	25.25
21P	25.00	28.00	26.50
25P	30.00	33.00	31.50
30P	36.25	39.25	37.75

RoHS Compliant		HSM 玄茂科技股份有限公司 HSUAN MAO TECHNOLOGY CO., LTD.	
APPD. 核准 HELEN	SCALE 比例 參考	TOLERANCE 容許公差 X.X±0.25 X.XX±0.15 X.XXX±0.05	PART NAME 品名 1.25mm HOUSING 1XXXP IVORY ROHS
DWG. 製圖 ABBY	UNIT 單位 MM	SIZE. 紙張尺寸 A4	PART NO. 料號 H1253-XXPI0000R
DATE 制表日 2015/10/16	PAGE 張數 1 OF 1	REV. 版次 A	