



SPECIFICATIONS

Current Rating: 1A AC,DC
 Voltage Rating: 150V AC,DC
 Temperature Range: -25°C ~ +85°C
 Contact Resistance: 30mΩ Max.
 Insulation Resistance: 500MΩ Min.
 Withstanding Voltage: 500V AC/minute
 Material: Nylon 66,UL94V-0
 Pantone Color: 7529C~7530C

Ordering Information & Dimensions

Pim	Dimensions	
	A	B
02P	1.25	4.15
03P	2.50	5.40
04P	3.75	6.65
05P	5.00	7.90
06P	6.25	9.15
07P	7.50	10.40
08P	8.75	11.65
09P	10.00	12.90
10P	11.25	14.15
11P	12.50	15.40
12P	13.75	16.65
13P	15.00	17.90
14P	16.25	19.15
15P	17.50	20.40

RoHS Compliant		玄茂科技股份有限公司 HSUAN MAO TECHNOLOGY CO., LTD.	
APPD. 核准 Angel	 SCALE 比例 參考 UNIT 單位 M M PAGE 張數 1 OF 1	TOLERANCE 容許公差 .0 ±0.25 .00 ±0.15 ANG. ±	PART NAME 品名 1.25mm HOUSING XXP
DWG. 製圖 Yumi		SIZE. 紙張尺寸 A 4	IVORY ROHS LOW-LEAD
DATE 制表日 2008/05/27	REV. 版次 A	PART NO. 料號 H1255-XXPSI000R	