



* Material: PA66 UL 94V-0 Black

SPECIFICATIONS

- * Current rating: 1A AC DC
- * Voltage rating: 100V AC DC
- * Temperature range: -25°C~+85°C
- * Insulation resistance: 1,000MΩ min.

CIRCUITS	Dim. A	Dim. B	CIRCUITS	Dim. A	Dim. B
16P	8.89	11.29	60P	36.83	39.23
18P	10.16	12.56	62P	38.10	40.50
20P	11.43	13.83	64P	39.37	41.77
22P	12.70	15.10	66P	40.64	43.04
24P	13.97	16.37	68P	41.91	44.31
26P	15.24	17.64	70P	43.18	45.58
28P	16.51	18.91	72P	44.45	46.85
30P	17.78	20.18	74P	45.72	48.12
32P	19.05	21.45	76P	46.99	49.39
34P	20.32	22.72	78P	48.26	50.66
36P	21.59	23.99	80P	49.53	51.93
38P	22.86	25.26	82P	50.80	53.20
40P	24.13	26.53	84P	52.07	54.47
42P	25.40	27.80	86P	53.34	55.74
44P	26.67	29.07	88P	54.61	57.01
46P	27.94	30.34	90P	55.88	58.28
48P	29.21	31.61	92P	57.15	59.55
50P	30.48	32.88	94P	58.42	60.82
52P	31.75	34.15	96P	59.69	62.09
54P	33.02	35.42	98P	60.96	63.36
56P	34.29	36.69	100P	62.23	64.63
58P	35.56	37.96			

RoHS Compliant		HSM 玄茂科技股份有限公司 HSUAN MAO TECHNOLOGY CO., LTD.	
APPD. 核准		TOLERANCE 容許公差	PART NAME 品名
DWG. 製圖	SCALE 比例	.0 ± 0.30 .00 ± 0.20 ANG. ± 3°	1.27mm FFC/FPC HOUSING DUAL ROW 2XXXP WITH LOCKING RIBS PA66UL94-V0 BLACK INSULATOR ROHS
DATE 制表日	UNIT 單位	SIZE. 紙張尺寸	PART NO.
2017/08/18	M M	A 4	料號 H1272-XXPYBA00R
Betty	PAGE 張數	REV. 版次	
	1 OF 1	A	