



**SPECIFICATIONS**

Current Rating: 3A AC,DC  
 Voltage Rating: 300V AC,DC  
 Temperature Range: -25°C ~ +85°C  
 Contact Resistance: 20mΩ Max  
 Insulation Resistance: 100MΩ Min  
 Withstanding Voltage: 1000V AC/minute  
 Material: Nylon 66,UL94V-0  
 Pantone Color: 153C~154C

**Ordering Information & Dimensions**

PIN NO.	Dimensions	
	A	B
02P	2.00	5.60
03P	4.00	7.60
04P	6.00	9.60
05P	8.00	11.60
06P	10.00	13.60
07P	12.00	15.60
08P	14.00	17.60
09P	16.00	19.60
10P	18.00	21.60
11P	20.00	23.60
12P	22.00	25.60
13P	24.00	27.60
14P	26.00	29.60
15P	28.00	31.60

RoHS Compliant	<b>HSM</b> 玄茂科技股份有限公司 HSUAN MAO TECHNOLOGY CO., LTD.		
APPD. 核准 Hedy	 TOLERANCE 容許公差 X.X±0.25 X.XX±0.15 X.XXX±0.05	PART NAME 品名 2.0mm HOUSING 1XXP BROWN COLOR LOW-LEAD	
DWG. 製圖 Yumi		SCALE 比例 參考	PART NO. H2004-XXPN0000R 料號
DATE 制表日 2009/09/16	UNIT 單位 MM	SIZE 紙張尺寸 A4	
	PAGE 張數 1 OF 1	REV. 次 A	