



**Features:**

- 2 ~ 4 circuits available
- Body: PBT + 15%GF, White
- Waterproof plug: Oil silicone, Light blue
- Disconnectable crimp style
- Waterproof grade: IPX7 of IEC 60529

**Specification:**

- Current rating: 3A AC, DC ( #22 AWG )
- ② • Voltage rating: 250V AC, DC
- ① • Insulation resistance: 1000MΩ Min.
- ② • Dielectric withstanding voltage: 1500V AC/minute
- ③ • Ambient temperature range: -40°C ~ 105°C  
(Including temperature rise)

**Dimensional Information ( mm )**

Circuits	Dim. A	Dim. B	Dim. C	Dim. D	Dim. E	Dim. F
2	2.0	4.7	6.7	4.7	5.5	7.0
3	4.0	6.7	8.7	4.7	5.5	7.0
4	6.0	8.7	10.7	4.7	5.5	7.0

RoHS Compliant		<b>HSM</b> 玄茂科技股份有限公司 HSUAN MAO TECHNOLOGY CO., LTD.	
APPD. 核准	SCALE 比例 參考	UNLESS OTHERWISE SPECIFIED TOLERANCE .000 ± 0.08 ( mm ) .00 ± 0.25 ( mm ) .0 ± 0.4 ( mm )	PART NAME 品名 2.0MM WATERPROOF CRIMP TERMINAL HOUSING MALE XXPIN BODY MATERIAL :PBT BODY COLOR:WHITE WATERPROOF PLUG :LIGHT BLUE(MATERIAL:OIL SILICONE) ROHS
DWG. 製圖 Betty	UNIT 單位 M M	SIZE. 紙張尺寸 A 4	PART NO. 料號 H2016-XXPPW700R
DATE 制表日 2020/10/27	PAGE 張數 1 OF 1	REV. 版次 A	