



Specification:

- 1、Material:PA66 UL94V-2
- 2、Current rating: 3A max
- 3、Voltage rating:250V AC/DC
- 4、Temperature range:-25℃to+85℃
- 5、Contact resistance:≤20mΩ
- 6、Insulation resistance:≥1000MΩ
- 7、Withstand voltage:800V AC/minute

未注公差表 UNTOLERANCE TABLE	
≤3	± 0.1
≤10	± 0.2
≤20	± 0.3
≤35	± 0.4
≤50	± 0.5
≤75	± 0.6
≤100	± 0.8
ANGLE	± 5°

6Pin

8Pin~14Pin

A	4.0	6.0	8.0	10.0	12.0	14.0	16.0	18.0	20.0	22.0	28.0	38.0
B	6.4	8.4	10.4	12.4	14.4	16.4	18.4	20.4	22.4	24.4	30.4	40.4
C	8.0	10.0	12.0	14.0	16.0	18.0	20.0	22.0	24.0	26.0	32.0	42.0
PIN	6	8	10	12	14	16	18	20	22	24	30	40

RoHS Compliant		HSM 玄茂科技股份有限公司 HSUAN MAO TECHNOLOGY CO., LTD.	
APPD. 核准	SCALE 比例 参考	PART NAME 品名	PAD 2.0MM HOUSING 2XXXPIN
DWG. 製圖 Betty	UNIT 單位 M M	MATERIAL:PA66 UL94V-2	WHITE COLOR ROHS
DATE 制表日 2022/03/22	PAGE 張數 1 OF 1	SIZE. 紙張尺寸 A 4	PART NO. 料號 H2021-XXPDW000R
		REV. 版次 A	