



MATERIAL: NYLON66 UL94V-2

VOLTAGE RATING: AC/250V, DC/350V

CURRENT RATING: AC, DC, 15A

INSULATION RESISTANCE: 1.000M Ω MIN.

WITHSTAND VOLTAGE: 1.500V AC/MINUTE

TEMPERATURE RANGE: -25°C TO +85°C

DIMENSION: (MM)

P: 5.03 \pm 0.1

L: 22.0 \pm 0.2

W: 6.0 \pm 0.2

H: 25.7 \pm 0.3

H1: 11.2 \pm 0.2

RoHS
Compliant

HSM 玄茂科技股份有限公司
HSUAN MAO TECHNOLOGY CO., LTD.

APPD.
核准
DWG.
製圖
DATE 制表日
2013/3/27

SCALE
比例
UNIT
單位
PAGE
張數
1 OF 1

TOLERANCE
容許公差
0 \pm 0.2
.00 \pm
ANG. \pm
SIZE.
紙張尺寸
A 4
REV.
版本
A

PART NAME 品名
6.3mm 2.36 ϕ MALE HOUSING 1X4P
W/ RIGHT ANGLE EAR WHITE COLOR
ROHS
PART NO.
料號
H2130-04PSRW00R

A

B

C

D

E

F

G

H

A

B

C

D

E

F

G

H

1

2

3

4

5

6

7

8

1

2

3

4

5

6

7

8