



L1=CIRCUITS -1 X P			
CIRCUITS L			
2	8.20	12	47.80
3	12.16	13	51.76
4	16.12	14	55.72
5	20.08	15	59.68
6	24.04	16	63.64
7	28.00	17	67.60
8	31.96	18	71.56
9	35.92	19	75.52
10	39.88	20	79.48
11	43.84		

Dimension

P: 3.96 ±0.10	H: 16.00 ±0.30	W: 6.35 ±0.30
L: **** ±0.50	L1: **** ±0.35	

H 2410 - 02 P N W 0 0 0 R

- 1. PRODUCTS: H:Housing
- 2. SERIES NO.: 2410
- 3. CONTACT NO.: 02-20
- 4. CONTACT TYPE: P:Non Distribution
- 5. BODY OPTION: N:W/O Locking Rib
- 6. INSULATOR COLOR: W:White(Standard)
- 7. FILL IT WITH*0*
- 8. FILL IT WITH*0*
- 9. FILL IT WITH*0*
- 11.R:ROHS

MATERIAL : NYLON 66 UL94V-2
 INSULATION RESISTANCE : 1000 M Ω MIN
 WITHSTANDING VOLTAGE : 1000V AC/MINUTE
 TEMPERATURE RANGE : -25°C TO +85°C
 CURRENT RATING : 7A AC/DC
 VOLTAGE RATING : 250V AC/DC

RoHS Compliant		HSM 玄茂科技股份有限公司	
		HSUAN MAO TECHNOLOGY CO., LTD.	
APPD. 核准		TOLERANCE 容許公差	PART NAME 品名
DWG. 製圖		SCALE 比例	3.96mm HOUSING XXP WITHOUT LOCKING RIBS WHITE INSULATOR ROHS
DATE 制表日	UNIT 單位	SIZE. 紙張尺寸	PART NO. 料號
2017/03/08	M M	A 4	H2410-XXPNW000R
	PAGE 張數	REV. 版次	
	1 / 1	A	