



SPECIFICATIONS

Current Rating: 4A AC,DC
 Voltage Rating: 250V AC,DC
 Temperature Range: -25°C ~ +85°C
 Contact Resistance: 10mΩ Max
 Insulation Resistance: 1000MΩ Min
 Withstanding Voltage: 1000V AC/minute
 Material: Nylon 66,UL94V-2
 Pantone Color: 1685C

Circuit No.	Dimensions		Circuit No.	Dimensions	
	A	B		A	B
02P	2.54	5.68	12P	27.94	31.08
03P	5.08	8.22	13P	30.48	33.62
04P	7.62	10.76	14P	33.02	36.16
05P	10.16	13.30	15P	35.56	38.70
06P	12.70	15.84	16P	38.10	41.24
07P	15.24	18.38	17P	40.64	43.78
08P	17.78	20.92	18P	43.18	46.32
09P	20.32	23.46	19P	45.72	48.86
10P	22.86	26.00	20P	48.26	51.40
11P	25.40	28.54			

RoHS
Compliant

HSM 玄茂科技股份有限公司
HSUAN MAO TECHNOLOGY CO., LTD.

APPD. 核准 HELEN
 DWG. 製圖 ABBY
 DATE 制表日 2013/12/25

SCALE 比例 參考
 UNIT 單位 M M
 PAGE 張數 1 OF 1

TOLERANCE 容許公差
 X.X±0.25
 X.XX±0.15
 X.XXX±0.05
 SIZE 紙張尺寸 A 4
 REV. 版次 A

PART NAME 品名
**2.54mm HOUSING 1XXP W/LOCKING RIBS
 W/POLARIZING RIBS NYLON 66 UL94V-2
 BROWN INSULATOR ROHS LOW-LEAD**
 PART NO. 料號
H2415-XXPYN000R