



Features:

- * Available in 4 Circuits
- * Nylon 66 UL94V-2 or Nylon 66 UL94V-0
- * Tolerance±0.2

Specifications:

- * Pitch between poles 5.08mm
- * Rated Voltage 250V AC,DC
- * Rated Current 7A
- * Applicable Wire AWG18~22

Dimensional & Ordering Information:

Wire Rang	D	Cover	Color	Material	
				Contact	Housing
AWG #18	0.6	—	Natural	Brass. Pre. Tin-Plated	Nylon 66 UL 94V-2
AWG #20	0.5	—	Natural	Brass. Pre. Tin-Plated	
AWG #22	0.4	—	Natural	Brass. Pre. Tin-Plated	
—	—	—	Natural	—	Nylon 66 UL 94V-2
—	—	—	Natural	—	

RoHS Compliant	HSM 玄茂科技股份有限公司 HSUAN MAO TECHNOLOGY CO., LTD.	
	APPD. 核准 DWG. 製圖 DATE 制表日 2020/3/10	SCALE 比例 UNIT 單位 PAGE 張數 1 OF 1
PART NAME 品名 5.08mm HOUSING 4P TIN PLATED WHITE INSULATOR ROHS		
PART NO. 料號 H2431-04PXWX00R		