




1 2 3 4 5 6 7 8



A  
B  
C  
D  
E  
F  
G  
H

A  
B  
C  
D  
E  
F  
G  
H



\* Poles:2~25  
\* Material:PBT UL94V-0 ,BLACK

Specifications  
\* Current rating: 2.5A AC, DC  
\* Voltage rating: 250V AC, DC  
\* Temperature range: -25°C~+85°C  
\* Insulation resistance: 1,000MΩ min.  
\* Withstand voltage: 800V AC/minute



CIRCUITS	DIMENSION in.(mm)		CIRCUITS	DIMENSION in.(mm)	
	A	B		A	B
2	0.100(2.54)	0.205(5.2)	14	1.300(33.02)	1.409(35.8)
3	0.200(5.08)	0.307(7.8)	15	1.400(35.54)	1.508(38.3)
4	0.300(7.62)	0.406(10.3)	16	1.500(38.10)	1.610(40.9)
5	0.400(10.16)	0.508(12.9)	17	1.600(40.64)	1.709(43.4)
6	0.500(12.70)	0.606(15.4)	18	1.700(43.18)	1.811(46.0)
7	0.600(15.24)	0.709(18.0)	19	1.800(45.72)	1.909(48.5)
8	0.700(17.78)	0.807(20.5)	20	1.900(48.26)	2.012(51.1)
9	0.800(20.32)	0.909(23.1)	21	2.000(50.80)	2.110(53.6)
10	0.900(22.86)	1.008(25.6)	22	2.100(53.34)	2.213(56.2)
11	1.000(25.40)	1.106(28.1)	23	2.200(55.88)	2.311(58.7)
12	1.100(27.94)	1.209(30.7)	24	2.300(58.42)	2.409(61.2)
13	1.200(30.48)	1.307(33.2)	25	2.400(60.96)	2.512(63.8)

APPD. 核准 BETTY		SCALE 比例 参考	TOLERANCE 容許公差 .0 ± .00 ± ANG. ±	PART NAME 品名 2.54mm FFC/FPC HOUSING XPP WITH BUMP & WITH LOCKING RIBS PBT UL94-V0 BLACK INSULATOR ROHS
DWG. 製圖 BETTY				
DATE 制表日 2009/12/17		PAGE 張數 1 OF 1	REV. 版次 A	PART NO. 料號 H2550-XXPYB000R

RoHS Compliant **HSM** 玄茂科技股份有限公司  
HSUAN MAO TECHNOLOGY CO., LTD.

1 2 3 4 5 6 7 8