



**SPECIFICATION:**  
 PITCH BETWEEN POLES : 2.54mm  
 CURRENT RATING 3A  
 VOLTAGE RATING : 250V  
 CONTACT RESISTANCE : INITIAL VALUE/10mΩ max.  
 AFTER ENVIRONMENTAL TESTING/20mΩ max.  
 INSULATION RESISTANCE :1000 MΩ(min.)  
 WITHSTAND VOLTAGE : 800V AC/MINUTE  
 APPLICABLE WIRE: AWG#22 TO #28  
 TEMPERATURE RANGE : -25°C TO +85°C  
**FEATURES:**  
 AVAILABLE NUMBER OF CIRCUITS 2  
 MATERIAL : NYLON 66 UL94V-0

RoHS Compliant		<b>HSM</b> 玄茂科技股份有限公司 HSUAN MAO TECHNOLOGY CO., LTD.	
APPD. 核准	BETTY	 TOLERANCE: .000 ±0.08 .00 ±0.13 .0 ±0.25 SCALE 比例 參考	PART NAME 品名 JST RCY 2.54mm MALE HOUSING 2P RED COLOR NYLON 66 UL94V-0 ROHS
DWG. 製圖	BETTY		
DATE 制表日	2011/09/23	UNIT 單位	M M
		PAGE 張數	1 OF 1
		SIZE: 紙張尺寸	A 4
		REV. 版次	A
		PART NO. 料號	H2553-02PR1000R