



SPECIFICATIONS

Electrical

Current Rating: 5A AC, DC
 Voltage Rating: 250V AC, DC
 Operating Temp.: -25°C ~ +85°C
 Insulation Resistance: 1000MΩ/ min.
 Dielectric Withstanding Voltage: 1500V AC/ min.
 Contact Resistance: 10mΩ/ max.

Material

Material: Nylon66, UL94V-2

Poles	Dimension mm (in.)	
	A	B
2	5.08	10.16
3	10.16	15.24
4	15.24	20.32
5	20.32	25.40
6	25.40	30.48
7	30.48	35.56
8	35.56	40.64
9	40.64	45.72
10	45.72	50.80
12	55.88	60.96

RoHS
Compliant

HSM 玄茂科技股份有限公司
HSUAN MAO TECHNOLOGY CO., LTD.

APPD. 核准	BETTY	 TOLERANCE 容許公差 X.XX ± 0.3 X.X ± 0.5	PART NAME 品名 MX 5.08mm HOUSING 1X7P W/O LOCKING RIBS WHITE COLOR ROHS
DWG. 製圖	BETTY		
DATE 制表日	2010/11/15	UNIT 單位 M M	PART NO. 料號 H5080-XXPNW000R
		PAGE 張數 1 OF 1	