



**DIMENSION:(MM)**

P:2.5 ± 0.1  
 H:16.3 ± 0.3  
 H1:6.0 ± 0.3  
 W:6.5 ± 0.2

**A ± 0.3    B ± 0.2    C ± 0.3**

2Pin :	7.5	2.5	-
3Pin :	10.0	5.0	3.2
4Pin :	12.5	7.5	5.7
5Pin :	15.0	10.0	8.2
6Pin :	17.5	12.5	10.7
7Pin :	20.0	15.0	13.2

MATERIAL:NYLON66 UL94V-0  
 VOLTAGE RATING:AC,DC,250V  
 CURRENT RATING:AC,DC,3A  
 INSULATION RESISTANCE:1000MΩ.min.  
 WITHSTANDING VOLTAGE:1.000V AC/MINUTE  
 TEMPERATURE RANGE:-25° TO +85°

RoHS Compliant		<b>HSM</b> 玄茂科技股份有限公司 HSUAN MAO TECHNOLOGY CO., LTD.	
APPD. 核准		TOLERANCE 容許公差 .0 ± 0.30 .00 ± 0.20 ANG. ± 3°	PART NAME 品名 2.5mm HOUSING 1XXXPIN WHITE COLOR NYLON 66 UL94V-0 ROHS
DWG. 製圖 Betty	SCALE 比例 參考	UNIT 單位 MM	PART NO. 料號 H7002-XXPW1000R
DATE 制表日 2020/09/29	PAGE 張數 1 OF 1	REV. 版次 A	