



SPECIFICATIONS :

Voltage Rating: 250V AC / DC
 Current Rating: 2.5A AC / DC
 Withstanding Voltage: 1000V AC/minute
 Temperature Range: -25°C~+85°C
 Insulation Resistance: 1000MΩ Min.
 Contact Resistance: 20mΩ Max.

Material: Nylon66, UL94V-0
 Color: Black

Poles	Dimensions	
	A	B
02P	5.08	2.54
03P	7.62	5.08
04P	10.16	7.62
05P	12.70	10.16
06P	15.24	12.70
07P	17.78	15.24
08P	20.32	17.78
09P	22.86	20.32
10P	25.40	22.86
11P	27.94	25.40
12P	30.48	27.94
13P	33.02	30.48
14P	35.56	33.02
15P	38.10	35.56
16P	40.64	38.10
17P	43.10	40.64
18P	45.64	43.18
20P	50.72	48.26

RoHS Compliant	HSM 玄茂科技股份有限公司 HSUAN MAO TECHNOLOGY CO., LTD.	
	APPD. 核准 DWG. 製圖 DATE 制表日 2020/2/17	SCALE 比例 UNIT 單位 PAGE 張數 1 OF 1
Part Name 品名 2.54mm HOUSING 4P W/O BUMP & W/O LOCKING RIBS BLACK COLOR MATERIAL: NYLON 66 ROHS		Part No. 料號 H7068-XXPB0000L