



FEATURES:

- . 2-25 Circuits
- . With or Without locking ramp and Polarizing Rib
- . Mates with .045" [1.14mm] pins
- . Through and end Type
- . Terminal Retention to Housing 8lbs [3.63kg] minimum

SPECIFICATIONS:

- . Current rating: 7A AC, DC
- . Voltage rating: 250V AC, Maximum
- . Temperature range: -40°C ~ +105°C .
- . Contact resistance: Initial Value/10mΩ max.
After environmental testing /20mΩ max.
- . Insulation resistance: 1000 MΩ min
- . Withstand Voltage: 1500V AC/minute
- . Applicable wire: AWG #18 ~ #26

Circuits	DIM.A	DIM.B
02	7.92	3.96
03	11.88	7.92
04	15.84	11.88
05	19.80	15.84
06	23.76	19.80
07	27.72	23.76
08	31.68	27.72
09	35.64	31.68
10	39.60	35.64
11	43.56	39.60
12	47.52	43.56
13	51.48	47.52

Circuits	DIM.A	DIM.B
14	55.44	51.48
15	59.40	55.44
16	63.36	59.40
17	67.32	63.36
18	71.28	67.32
19	75.24	71.28
20	79.20	75.24
21	83.16	79.20
22	87.12	83.16
23	91.08	87.12
24	95.04	91.08
25	99.00	95.04

<p>RoHS Compliant</p>		<p>HSM 玄茂科技股份有限公司 HSUAN MAO TECHNOLOGY CO., LTD.</p>	
<p>APPD. 核准 BETTY</p>		<p>TOLERANCE 容許公差 .0 ± .00 ± ANG. ±</p>	<p>PART NAME 品名 3.96mm HOUSING XXP XX AWG TIN PLATED WHITE COLOR(UL94V2) ROHS</p>
<p>DWG. 製圖 KAREN</p>	<p>SCALE 比例 參考</p>	<p>UNIT 單位 MM</p>	<p>SIZE 紙張尺寸 A4</p>
<p>DATE 制表日 2013/11/22</p>	<p>PAGE 張數 1 OF 1</p>	<p>REV. 版本 A</p>	<p>PART NO. 料號 H8396-XXPXTWXXR</p>