



■ **PLUG HOUSING**

- **Material & Finish:**
 Insulator①: Thermal Plastic, UL 94V-0
 Shell ② : Copper Alloy, Ni plated
- **Pitch :** 1.00mm (.039")
- **Poles :** 14, 20, 30

■ **SPECIFICATIONS**

- **Voltage rating:** 50V AC/DC
- **Current rating:** 1A (AWG#28)
- **Withstand Voltage:** 500V AC/minute
- **Contact resistance:** 20m Ohm max.
- **Insulation Resistance:** 100M Ohm min.
- **Temperature Range:** -25 ~ +85°C

CIRCUITS	DIMENSION			
	A	B	C	D
14	17.5	13.00	14.5	15.9
20	23.5	19.00	20.5	21.9
30	33.5	29.00	30.5	31.9

RoHS Compliant		HSM 玄茂科技股份有限公司		HSUAN MAO TECHNOLOGY CO., LTD.	
APPD. 核准 HELEN	SCALE 比例 參考	TOLERANCES UNLESS NOTED		PART NAME 品名	
DWG. 製圖 ABBY		LINEAR ± .x ±0.3 .xx ±0.15 .xxx±0.08	DF19 1.0mm HOUSING 1XXXP SINGLE ROW WHITE COLOR ROHS		
DATE 制表日 2012/08/07	UNIT 單位 MM	ANGLES ± 2°	SIZE. 紙張尺寸 A4	PART NO. 料號 H9012-XXPSW000R	
	PAGE 張數 1 OF 1	REV. 版次 B			