



Specifications
 Voltage Rating: 50V AC/ DC
 Current Rating: 1A AC/DC
 Withstanding Voltage: 500V AC/Minute
 Insulation Resistance: 100MΩ Min.
 Temperature Range: -25° C~+85° C
 Contact Resistance: 20mΩ Max.
 Material: PBT, UL94V-0
 Color: Nature
 Q'ty/Bag: 1000PCS

Ordering Information & Dimensions

Poles	Dimensions (mm)		
	A	B	C
2	1.00	3.00	2.40
3	2.00	4.00	3.40
4	3.00	5.00	4.40
5	4.00	6.00	5.40
6	5.00	7.00	6.40
7	6.00	8.00	7.40
8	7.00	9.00	8.40
9	8.00	10.00	9.40
10	9.00	11.00	10.40
11	10.00	12.00	11.40
12	11.00	13.00	12.40
14	13.00	15.00	14.40
15	14.00	16.00	15.40

APPD. 核准 Betty		TOLERANCE 容許公差 .0 ± 0.30 .00 ± 0.20 ANG. ± 3°	PART NAME 品名 1.0mm HOUSING 1XXXP WITHOUT LOCKING RIB PBT UL94V-0 WHITE COLOR ROHS
DATE 制表日 2019/6/24	UNIT 單位 MM	REV. 版次 B	PART NO. 料號 H9015-XXPNPW00R
RoHS Compliant		HSM 玄茂科技股份有限公司 HSUAN MAO TECHNOLOGY CO., LTD.	
PAGE 張數 1 OF 1			