



SPECIFICATIONS

Electrical

- Current Rating: 1A AC, DC
- Voltage Rating: 100V AC, DC.
- Operating Temp.: $-25^{\circ}\text{C} \sim +85^{\circ}\text{C}$
- Insulation Resistance: $500\text{M}\Omega / \text{min.}$
- Dielectric Withstanding Voltage: $500\text{V AC} / \text{min.}$
- Contact Resistance: $20\text{M}\Omega / \text{max.}$

Material

- Terminal material: Phosphor Bronze/ Tin-plated
- Wire Range: 28 to 32AWG

| | | | |
|------------------------|--|---|--|
| RoHS Compliant | | HSM 玄茂科技股份有限公司 HSUAN MAO TECHNOLOGY CO., LTD. | |
| APPD. 核准 Angel | SCALE 比例 参考 UNIT 單位 M M PAGE 張數 1 OF 1 | TOLERANCE 容許公差 .0 ± 0.15 .00 ± 0.25 ANG. \pm | PART NAME 品名 1.25mm FOR BOARD IN TERMINAL PHOSPHOR BRONZE MATERIAL TIN PLATING SUITABLE AWG28~32 1R=15K PCS ROHS LOW-LEAD |
| DWG. 製圖 Yumi | | SIZE. 紙張尺寸 A 4 | PART NO. 料號 T1026-TPP00000R |
| DATE 制表日 2008/08/20 | | REV. 版次 A | |