



**Specification**

- 1.Current Rating:2.0A AC/DC, AWG#28~#30
- 2.Voltage Rating:50V AC/DC
- 3.Contact Resistance:10mΩ Max.
- 4.Insulation Resistance:100MΩ Min.
- 5.Dielectric Withstanding Voltage: 500 VAC Minute
- 6.Operating Temperature:-25℃~85℃

**Material:**  
1.Contact:Copper Alloy T=0.12mm

**Finish:**  
1.Contact:Gold Flash Over Nickel

**Specifications Information:**

Thickness	Material	Wire Range	Finish	Q'ty / Reel
0.12mm	PHOS.	AWG #28~30	See P/N Option	20000pcs

RoHS Compliant		<b>HSM</b> 玄茂科技股份有限公司 HSUAN MAO TECHNOLOGY CO., LTD.	
APPD. 核准 Betty	SCALE 比例 参考	TOLERANCE 容許公差 .0 ± 0.30 .00 ± 0.20 ANG. ± 3°	PART NAME 品名 1.2mm TERMINAL MATERIAL:PHOSPHOR BRONZE GOLD FLASH PLATING SUITABLE AWG28~30 ROHS
DWG. 製圖 Betty		UNIT 單位 M M	PART NO. 料號 T1200-GPS00000R
DATE 制表日 2013/12/16	PAGE 張數 1 OF 1	SIZE 紙張尺寸 A 4	REV. 版次 A