



MATERIAL:BRASS
 THICKNESS:0.25
 HARDNESS:SH
 PLATING:TIN 40u' MIN
 WIRE RANGE:(AWG)18-24
 INSULATION O.D.:3.8 MAX.
 VOLTAGE RATING:AC/250V,DC/350V
 CURRENT RATING:AC,DC,7A
 TEMPERATURE RANGE : -25°C TO +85°C

DIMENSION:(MM)

T:0.25 ± 0.03
 L:22.0 ± 0.3
 E:11.2 ± 0.4
 IS:4.2 ± 0.3
 WS:3.3 ± 0.3
 H:3.5 ± 0.25
 H1:3.1 ± 0.25
 H2:1.2 ± 0.25
 W:3.0 ± 0.15
 W1:3.6 ± 0.25
 W2:4.2 ± 0.3
 D:3.05-3.15
 D1:2.65-2.8
 e:8.4 ± 0.25

RoHS Compliant		HSM 玄茂科技股份有限公司 HSUAN MAO TECHNOLOGY CO., LTD.	
APPD. 核准 Angel		TOLERANCE 容許公差 .0 ± .00 ± ANG. ±	PART NAME 品名 MX φ2.36mm FEMALE TERMINAL BRASS MATERIAL TIN PLATING AWG18~24 1ROLL=5000PCS ROHS LOW-LEAD
DWG. 製圖 Yumi	SCALE 比例 參考	SIZE. 紙張尺寸 A 4	PART NO. 料號 T2130-TBE00000R
DATE 制表日 2010/07/14	UNIT 單位 MM	REV. 版次 A	
	PAGE 張數 1 OF 1		