



■ SPECIFICATIONS

- Current Rating : 1A AC/DC Δ
- Withstanding Voltage : 250V AC /minute
- Insulation Resistance : 100M Ω min
- Temperature Range : - 40 $^{\circ}$ C to + 85 $^{\circ}$ C
- Contact Resistance : 20m Ω max

■ WAFER

- ① Poles No. : 02~15
- ② Base Material : Nylon 46 UL94V-0, Color : Nature
- ③ PIN Material : Brass
- ④ Plated : Tin Plated
- ⑤ Packing : Paper Ree; Q'ty 1000Pcs/Reel

Poles	Dimensions (mm)			
	A	B	C	D
2	1.25	4.25	3.05	7.65
3	2.50	5.50	4.30	8.90
4	3.75	6.75	5.55	10.15
5	5.00	8.00	6.80	11.40
6	6.25	9.25	8.05	12.65
7	7.50	10.50	9.30	13.90
8	8.75	11.75	10.55	15.15
9	10.00	13.00	11.80	16.40
10	11.25	14.25	13.05	17.65
11	12.50	15.50	14.30	18.90
12	13.75	16.75	15.55	20.15
13	15.00	18.00	16.80	21.40
14	16.25	19.25	18.05	22.65
15	17.50	20.50	19.30	23.90

RoHS Compliant

HSM 玄茂科技股份有限公司
HSUAN MAO TECHNOLOGY CO., LTD.

APPD. 核准
Betty
DATE 制表日
2020/06/10

SCALE 比例 参考
UNIT 單位 M M
PAGE 張數 1 OF 1
TOLERANCE
.0 ± 0.30
.00 ± 0.20
.000 ± 0.10
ANGLE
0 $^{\circ}$ $\pm 1^{\circ}$
SIZE 紙張尺寸 A 4
REV. 版次 D

PART NAME 品名
1.25mm WAFER SMT STRAIGHT TYPE
1XXXPTIN PLATED IVORY COLOR
ROHS
PART NO.
料號 W1359-XXPATXI0R