



- SPECIFICATIONS**
- Current Rating : 1A AC/DC
 - Withstanding Voltage : 250V AC /minute
 - Insulation Resistance : 100MΩ min
 - Temperature Range : - 40℃ to + 85℃
 - Contact Resistance : 20mΩ max

- WAFER**
- Material :
 - Poles No. : 02-15
 - Base Material : Nylon 46 UL94V-0, Color : Nature
 - Contact : Brass
 - Solder Nail : Brass
 - Plated : Tin Plated
 - Q' ty : 1,500 pcs./Tape & Reel

4

Poles	Dimensions (mm)			
	A	B	C	D
2	1.25	4.25	3.05	7.10
3	2.50	5.50	4.30	8.35
4	3.75	6.75	5.55	9.60
5	5.00	8.00	6.80	10.85
6	6.25	9.25	8.05	12.10
7	7.50	10.50	9.30	13.35
8	8.75	11.75	10.55	14.60
9	10.00	13.00	11.80	15.85
10	11.25	14.25	13.05	17.10
11	12.50	15.50	14.30	18.35
12	13.75	16.75	15.55	19.60
13	15.00	18.00	16.80	20.85
14	16.25	19.25	18.05	22.10
15	17.50	20.50	19.30	23.35

RoHS Compliant **HSM 玄茂科技股份有限公司**
HSUAN MAO TECHNOLOGY CO., LTD.

APPD. 核准 HELEN	SCALE 比例 參考	TOLERANCE .0 ±0.30 .00 ±0.20 .000 ±0.10	PART NAME 品名 1.25mm WAFER SMT RIGHT ANGLE 1XXXP TIN PLATED IVORY COLOR ROHS
DWG. 製圖 ABBY	UNIT 單位 M M	ANGLE 0° ±1°	PART NO. 料號 W1359-XXPBTXI0R
DATE 制表日 2013/05/10	PAGE 張數 1 OF 1	SIZE 紙張尺寸 A 4	REV. 版次 A