



NO. OF CONTACT	Dimension		NO. OF CONTACT	Dimension	
	A	B		A	B
02	3.96	8.06	10	35.64	39.74
03	7.92	12.02	11	39.60	43.70
04	11.88	15.98	12	43.56	47.66
05	15.84	19.94	13	47.52	51.62
06	19.80	23.90	14	51.48	55.58
07	23.76	27.86	15	55.44	59.54
08	27.72	31.82	16	59.40	63.50
09	31.68	35.78			

NOTES:

SPECIFICATION

1. Current : 4A max.
2. Voltage: 250V AC max.
3. Insulation Resistance: 1000 Megohms Min.
4. Contact Resistance: 10 Milliohms Max.
5. Dielectric Withstanding Voltage: 1000V AC
6. Operating Temperature: 0°C to +50°C

MATERIAL

1. Contact: Brass
2. Housing: Nylon, UL 94V-2

<p>RoHS Compliant</p>		<p>HSM 玄茂科技股份有限公司 HSUAN MAO TECHNOLOGY CO., LTD.</p>	
<p>APPD. 核准 HELEN</p>	<p>SCALE 比例 參考</p>	<p>TOLERANCE 容許公差 .0 ±0.35 .00 ±0.10 ANG ±</p>	<p>PART NAME 品名 3.96mm WAFER 1XXXP STRAIGHT TYPE W/O LOCKING RIBS WHITE INSULATOR ROHS</p>
<p>DWG. 製圖 ABBY</p>	<p>UNIT 單位 MM</p>	<p>SIZE. 紙張尺寸 A4</p>	<p>PART NO. 料號 W1396-XXPCNXW0R</p>
<p>DATE 制表日 2014/05/22</p>	<p>PAGE 張數 1 OF 1</p>	<p>REV. 版次 A</p>	