



■ SPECIFICATIONS

- Current Rating : 3A AC/DC
- Voltage Rating : 125V AC/DC
- Withstanding Voltage : 500V AC/minute
- Insulation Resistance : 1000MΩ min.
- Temperature Range : -40℃ to +105℃
- Contact Resistance : 20mΩ max.

■ Wafer

Product Code

- ① Poles: 02~15
- ② Base : PA9T UL94 V-0 Color: Natural

• Material :

1. Contact : Phosphor Bronze Matte Tin Plated
 2. Base : Refer the above options
 3. Solder Tab: Brass Matte Tin Plated
- Packing : Reel

Poles	Dimensions (mm)		
	A	B	C
02	2.00	10.90	4.80
03	4.00	12.60	6.80
04	6.00	14.60	8.80
05	8.00	16.60	10.80
06	10.00	18.60	12.80
07	12.00	20.60	14.80
08	14.00	22.60	16.80
09	16.00	24.60	18.80
10	18.00	26.60	20.80
11	20.00	28.60	22.80
12	22.00	30.60	24.80
13	24.00	32.60	26.80
14	26.00	34.60	28.80
15	28.00	26.60	30.80

RoHS Compliant

HSM 玄茂科技股份有限公司
HSIUAN MAO TECHNOLOGY CO., LTD.

APPD. 核准
 Betty
 DWG. 製圖
 DATE 制表日
 2023/08/22

SCALE 比例 參考
 UNIT 單位 MM
 PAGE 張數 1 OF 1

TOLERANCE
 .0 ±0.30
 .00 ±0.20
 .000 ±0.10
 ANGLE
 0° ±1°
 SIZE 紙張尺寸 A4
 REV. 版次 A

PART NAME 品名
 2.0MM WAFER 1XXXPIN SMT STRAIGHT
 TYPE MATTE TIN PLATING MATERIAL: PA9T
 UL94V-0 WHITE INSULATOR REEL PACKING
 ROHS

PART NO. 料號
 W2041-XXPAZBCRR