



SPECIFICATIONS
 Current Rating: 7A AC,DC
 Voltage Rating: 600V AC,DC
 Temperature Range: -25°C ~ +85°C
 Contact Resistance: 3mΩ Max
 Insulation Resistance: 5000MΩ Min
 Withstanding Voltage: 2200V AC/minute
 Pin Material: Brass/Tin-plated
 Material: Nylon 66,UL94V-0
 Color: Natural(White)

Ordering Information

PART NO.	Dimensions	
	A	B
02P	3.96	7.92
03P	7.92	11.88
04P	11.88	15.84
05P	15.84	19.80
06P	19.80	23.76
07P	23.76	27.72
08P	27.72	31.68
09P	31.68	35.64
10P	35.64	39.60
11P	39.60	43.56
12P	43.56	47.52
13P	47.52	51.48
14P	51.48	55.44
15P	55.44	59.40
16P	59.40	63.36
17P	63.36	67.32
18P	67.32	71.28
19P	71.28	75.24
20P	75.24	79.20

APPD. 核准 Hedy DWG. 製圖 Yumi DATE 制表日 2008/06/16		HSM 玄茂科技股份有限公司 HSUAN MAO TECHNOLOGY CO., LTD.		PART NAME 品名 3.96mm WAFER STRAIGHT TYPE XXP Square Pin WITH LOCKING RIBS TIN PLATED WHITE COLOR ROHS
		TOLERANCE 容許公差 .0 ±0.25 .00 ±0.15 ANG. ±	SCALE 比例 參考 UNIT 單位 MM PAGE 張數 1 OF 1	SIZE 紙張尺寸 A 4 REV. 版次 A