



P. C. board hole dimensions

**Features:**

- 2 ~ 4 circuits available
- Plastic material: UL 94V-2 nylon
- Pin material: Tin-plated phosphor bronze

**Specification:**

- Current rating: 7A Max.
- Voltage rating: 250V AC, 175V DC
- Dielectric withstanding voltage: 1500V AC/minute
- Non operating temperature : -40°C ~ 105°C
- Operating temperature : 0°C ~ 75°C

**Dimensional Information ( mm )**

Circuits	Dim. A	Dim. B	Dim. C
2	5.08	10.84	15.24
3	10.16	15.92	20.32
4	15.24	21.00	25.40

<b>RoHS</b> Compliant	<b>HSM</b> 玄茂科技股份有限公司 <b>HSUAN MAO TECHNOLOGY CO., LTD.</b>	
	PART NAME 品名 5.08mm POWER HEADER(FEMALE) XXP STRAIGHT TYPE TIN PLATED WHITE ROHS	
APPD. 核准 DWG. 製圖 Hedy DATE 制表日 2015/10/21	UNLESS OTHERWISE SPECIFIED TOLERANCE .000 ± 0.08 ( mm ) .00 ± 0.25 ( mm ) .0 ± 0.40 ( mm )	PART NO. 料號 <b>W2440-XXPSTW00R</b>
SCALE 比例 參考 UNIT 單位 MM PAGE 張數 1 / 1	SIZE. 紙張尺寸 A 4 REV. 版次 A	