


Poles: 4  
 Material: Post: Brass, Tin/Plated  
 Base: Nylon 66, UL94V-2  
 Q'ty: 500 pcs/bag

### SPECIFICATIONS

Accepts cantilever crimp terminal  
 Housing Nylon 66 (UL94V-2)  
 Mates with 0.084" (2.13mm) crimp terminal housing  
 Terminal Retention to housing-8lbs (3.63kg) min.  
 Voltage: rating: AC, DC, 250V  
 Current rating: 7A, AC, DC  
 Withstand voltage: 1500V AC/minute  
 Insulation resistance: 1000MΩ min  
 Temperature range: -25°C~+90°C  
 Contact resistance: Initial Valueable/10mΩ max.  
 After environmental testing/20mΩ max.



<b>RoHS Compliant</b>		<b>HSM 玄茂科技股份有限公司</b> <b>HSUAN MAO TECHNOLOGY CO., LTD.</b>	
APPD. 核准  DWG. 製圖 <i>Helen</i>	TOLERANCE 容許公差 0 ± 0.35 .00 ± 0.25 ANG. ± 3°	PART NAME 品名 5.08mm POWER PLUG 4P STRAIGHT TYPE TIN PLATED WHITE ROHS	
DATE 制表日 2022/11/23	SCALE 比例 參考  UNIT 單位 MM  PAGE 張數 1 OF 1	SIZE. 紙張尺寸 A4  REV. 版本 B	PART NO. 料號 W2470-04PSTW00R