



**Features:**

- 4 ~ 16 circuits available
- Housing material: LCP
- ⚠ Pin material: High conductivity copper alloy
- ⚠ Finished: Tin-plated 100u" over copper 50u"
- .025"(0.64mm) square pin

**Specification:**

- ⚠ Current rating: 8A at #16 AWG
- Voltage rating: 400V AC(RMS) or 400V DC Max.
- Contact resistance: 10mΩ Max.
- Dielectric withstanding voltage: 1800V AC/minute
- Ambient temperature range: -40°C ~ 105°C

**Ordering Information**

Part No.	Feature	Type	Color
W4352-XXPDSYTNBGR	With post	Key A	Black
W4352-XXPDSYTNCGR		Key B	Natural

&& xx = 04 ~ 16

**Dimensional Information ( mm )**

Circuits	Dim. A	Dim. B
4	3.5	8.0
6	7.0	11.5
8	10.5	15.0
10	14.0	18.5
12	17.5	22.0
14	21.0	25.5
16	24.5	29.0

RoHS Compliant

**HSM** 玄茂科技股份有限公司  
**HSUAN MAO TECHNOLOGY CO., LTD.**

APPD. 核准  
 DWG. 製圖 Betty  
 DATE 制表日  
 2020/01/14

UNLESS OTHERWISE SPECIFIED TOLERANCE  
 .000 ± 0.15 ( mm )  
 .00 ± 0.25 ( mm )  
 .0 ± 0.4 ( mm )

SCALE 比例 參考

UNIT 單位 M M

PAGE 張數 1 OF 1

SIZE 紙張尺寸 A 4

REV. 版次 A

PART NAME 品名  
 3.5mm Wafer Dual Row 2XXXPin 180°  
 With Locating Peg Tin Plating  
 Material:LCP Bag Packing ROHS

PART NO.  
 料號 W4352-XXPDSYTNXGR