



RECOMMENDED P.C. BOARD HOLE DIM.

### Specifications

#### Electrical

- Voltage Rating: 250V(AC)
- Current Rating: 7A
- Contact Resistance: 20m Ω max.
- Dielectric Withstanding Voltage: 1500V AC/1min.
- Insulation Resistance: 1000M Ω min.

#### Material

- Circuits: 2~10,12
- Insulator: Nylon 66 UL 94V-2
- Color: Natural
- Contact: Brass 1.14mm(0.45 ") Square Wire Pins
- Plating: Tin or Gold Plated
- Temperature Range: -25 °C~+85 °C

Poles	Dimension		Part NO.
	A	B	
2	5.08	10.22	02
3	10.16	15.30	03
4	15.24	20.38	04
5	20.32	25.46	05
6	25.40	30.54	06
7	30.48	35.62	07
8	35.56	40.70	08
9	40.64	45.78	09
10	45.72	50.86	10
12	55.88	60.96	12

<b>RoHS</b> Compliant	<b>HSM</b> 玄茂科技股份有限公司 <b>HSUAN MAO TECHNOLOGY CO., LTD.</b>		
	APPD. 核准 DWG. 製圖 DATE 制表日 2009/07/09	SCALE 比例 UNIT 單位 PAGE 張數 Hedy M M 1 / 1	TOLERANCE 容許公差 <b>X.XX ± 0.3</b> <b>X.X ± 0.5</b> SIZE. 紙張尺寸 A 4 REV. 版次 A
	PART NAME 品名 5.08mm WAFER RIGHT ANGLE TYPE XXP W/LOCKING RIB WHITE COLOR (V2 MATERIAL) LOW-LEAD		
	PART NO. 料號 W4508-XXPRYXW0R		