



### SPECIFICATIONS

#### Electrical

Current Rating: 5A AC, DC  
 Voltage Rating: 250V AC, DC  
 Operating Temp.: -25°C ~ +85°C  
 Insulation Resistance: 1000MΩ/ min.  
 Dielectric Withstanding Voltage: 1500V AC/ min.  
 Contact Resistance: 10mΩ/ max.

#### Material

Material: Nylon66, UL94V-0

Poles	Dimension mm (in.)	
	A	B
2	5.08	10.30
3	10.16	15.40
4	15.24	20.50
5	20.32	25.60
6	25.40	30.70
7	30.48	35.80
8	35.56	41.00
9	40.64	46.10
10	45.72	51.20

<b>RoHS Compliant</b>		<b>HSM 玄茂科技股份有限公司</b> <b>HSUAN MAO TECHNOLOGY CO., LTD.</b>	
APPD. 核准 BETTY DWG. 製圖 KAREN DATE 制表日 2013/07/26	TOLERANCE 容許公差 SCALE 比例 參考 UNIT 單位 MM PAGE 張數 1 OF 1	PART NAME 品名 5.08mm WAFER STRAIGHT TYPE 1*XXP W/O LOCKING RIB WHITE COLOR (V2) ROUND PIN:OD=1.13MM L=19 mm ROHS	PART NO. 料號 W4509-XXPSNXW0R