



SPECIFICATIONS
 Current Rating: 7A AC,DC
 Voltage Rating: 250V AC,DC
 Temperature Range: $-25^{\circ}\text{C} \sim +85^{\circ}\text{C}$
 Contact Resistance: 10m Ω Max
 Insulation Resistance: 1000M Ω Min
 Withstanding Voltage: 1500V AC/minute
 Pin Material: Brass/Tin-plated
 Material: Nylon 66,UL94V-2
 Color: Natural(Translucent)

Ordering Information & Dimensions

NO.	Dimensions	
	A	B
02P	5.08	8.20
03P	10.16	13.28
04P	15.24	18.36
05P	20.32	23.44
06P	25.40	28.52
07P	30.48	33.60
08P	35.56	38.68
09P	40.64	43.76
10P	45.72	48.84
11P	50.80	53.92
12P	55.88	59.00
13P	60.96	64.08
14P	66.04	69.16
15P	71.12	74.24
16P	76.20	79.32
17P	81.28	84.40

RoHS Compliant		HSM 玄茂科技股份有限公司 HSUAN MAO TECHNOLOGY CO., LTD.	
APPD. 核准 DWG. 製圖 HELEN DATE 制表日 2009/1/15	SCALE 比例 參考 UNIT 單位 M M PAGE 張數 1 OF 1	TOLERANCE 容許公差 0 ± 0.25 .00 ± 0.15 ANG. \pm SIZE. 紙張尺寸 A 4 REV. 版本 A	PART NAME 品名 5.08mm WAFER STRAIGHT TYPE 1X??P WITH SHORT LOCKING RIB TIN PLATING WHITE COLOR (V2) ROUND PIN OD=1.13MM L=19.5mm ROHS LOW-LEAD PART NO. 料號 W4509-XXPSYTWOR