



FEATURES:

- . 2-20 Circuits
- . .045" [1.14mm] Square wire pins
- . Nylon 66
- . Straight or Right angle pins
- . Mate with center crimp connector

SPECIFICATIONS:

- . Current rating: 7A AC. DC
- . Voltage rating: 250V AC. Maximum
- . Temperature range: -40°C ~ +105°C
- . Contact resistance: Initial Value/10mΩ max.
After environmental testing /20mΩ max.
- . Insulation resistance: 5000 MΩ min
- . Withstand voltage: 1500V AC/minute
- . Applicable PC board thickness: .063"[1.6mm]

PIN數	DIM.A	DIM.B
02	10.16	5.08
03	15.24	10.16
04	20.32	15.24
05	25.40	20.32
06	30.48	25.40
07	35.56	30.48
08	40.64	35.56
09	45.72	40.64
10	50.80	45.72
11	55.88	50.80

PIN數	DIM.A	DIM.B
12	60.96	55.88
13	66.04	60.96
14	71.12	66.04
15	76.20	71.12
16	81.28	76.20
17	86.36	81.28
18	91.44	86.36
19	96.52	91.44
20	101.6	96.52

RoHS Compliant		玄茂科技股份有限公司 HSUAN MAO TECHNOLOGY CO., LTD.	
APPD. 核准 Hedy	SCALE 比例 參考 UNIT 單位 M M PAGE 張數 1 OF 1	TOLERANCE 容許公差 .0 ±0.20 .00 ±0.10 ANG. ±	PART NAME 品名 5.08mm WAFER 1XXXPIN STRAIGHT TYPE WITHOUT BACK WHITE COLOR TIN PLATING ROHS
DWG. 製圖 Yumi		DATE 制表日 2008/08/28	SIZE. 紙張尺寸 A 4 REV. 版次 A