



**Specification:**

- 1、Material: Rubber shell:PA66 UL94V-2      PIN:H65 (Plating:SnSb)  
Material:Phosphor Bronze (QSn6.5-0.1/C5191)
- 2、Current rating: 20A max
- 3、Voltage rating: 300V AC/DC
- 4、Temperature range:-25°Cto+85°C
- 5、Contact resistance:≤10mΩ
- 6、Insulation resistance:≥1000MΩ
- 7、Withstand voltage:2000V AC/minute
- 8、Fixing force of pins: ≥25N
- 9、Applicable PC board thickness:1.6mm

<b>RoHS Compliant</b>				<b>TOLERANCE 容許公差</b> 0 ± 0.4 .00 ± 0.35 ANG. ± 5°		<b>PART NAME 品名</b> 6.2MM WAFER STRAIGHT TYPE DUAL ROW 2X6PIN W/ LOCKING RIBS TIN PLATING WHITE COLOR NY66 UL94V-2 BAG PACKING ROHS	
				<b>SCALE 比例 参考</b> UNIT 單位    M M PAGE 頁數    1 OF 1		<b>SIZE 線規尺寸 A 4</b> <b>REV. 版本 A</b>	
APPD. 核准 DWG. 製圖 DATE 制表日 2022/5/20		Helen		<b>HSM 玄茂科技股份有限公司</b> <b>HSUAN MAO TECHNOLOGY CO., LTD.</b>		<b>PART NO. 料號</b> W6211-12PDSTW0GR	