

Features:


- 2 ~ 6 circuits available
- UL 94V-2 nylon 66
- .045"(1.14mm) square pin
- Tin-plated brass pins. Plating options available
- Polarization through varied center spacing between circuit 1 and 2
- UL file No.: E114003
- CSA file No.: LR86545

Specifications:

- Current rating: 7A AC, DC
- Voltage rating: 250V AC, DC
- Contact resistance: 20mΩ Max.
- Dielectric withstanding voltage: 1500V AC/minute
- Ambient temperature range: -40°C ~ 105°C

Dimensional Information (mm)

Circuits	Dim. A	Dim. B	Circuits	Dim. A	Dim. B
2	7.5	12.5	5	22.5	27.5
3	12.5	17.5	6	27.5	32.5
4	17.5	22.5			



P. C. Board Hole Dimensions $\phi 1.8 \pm 0.05$

RoHS Compliant	HSM 玄茂科技股份有限公司 HSUAN MAO TECHNOLOGY CO., LTD.	
	APPD. 核准 DWG. 製圖 DATE 制表日 2013/10/24	Hedy M M 1 / 1
UNLESS OTHERWISE SPECIFIED TOLERANCE .000 ± 0.08 (mm) .00 ± 0.25 (mm) .0 ± 0.40 (mm)	SCALE 比例 參考 UNIT 單位 M M	SIZE. 紙張尺寸 A 4 REV. 版次 A