

P. C. B LAYOUT

Specifications

Voltage Rating: 125V AC/ DC

Current Rating: 1A AC/DC

Withstanding Voltage: 500V AC/Minute

Insulation Resistance: 100MΩ Min.

Temperature Range: -25° C~+85° C

Contact Resistance: 20mΩ Max.

Pin Material: Brass/Tin-plated

Material: Nylon 9T, UL94V-0

Q'ty/ Reel : 1500PCS


Ordering Information & Dimensions

Poles	Dimensions (mm)				
	A	B	C	D	E
2	1.00	3.70	2.50	3.00	3.70
3	2.00	4.70	3.50	4.00	4.70
4	3.00	5.70	4.50	5.00	5.70
5	4.00	6.70	5.50	6.00	6.70
6	5.00	7.70	6.50	7.00	7.70
7	6.00	8.70	7.50	8.00	8.70
8	7.00	9.70	8.50	9.00	9.70
9	8.00	10.70	9.50	10.00	10.70
10	9.00	11.70	10.50	11.00	11.70
11	10.00	12.70	11.50	12.00	12.70
12	11.00	13.70	12.50	13.00	13.70
13	12.00	14.70	13.50	14.00	14.70
14	13.00	15.70	14.50	15.00	15.70
15	14.00	16.70	15.50	16.00	16.70
16	15.00	17.70	16.50	17.00	17.70
17	16.00	18.70	17.50	18.00	18.70
18	17.00	19.70	18.50	19.00	19.70
19	18.00	20.70	19.50	20.00	20.70
20	19.00	21.70	20.50	21.00	21.70

RoHS
Compliant

HSM 玄茂科技股份有限公司
HSUAN MAO TECHNOLOGY CO., LTD.

APPD.
核准 Betty



TOLERANCE
容許公差
.0 ± 0.30
.00 ± 0.20
ANG. ± 3°

PART NAME 品名
1.0mm WAFER 1XXXXP SMT TOP ENTRY TYPE
TIN PLATING BEIGE COLOR
INSULATOR MATERIAL: NYLON 9T
FILM+REEL PACKING ROHS

DWG.
製圖

SCALE
比例 參考
UNIT
單位 MM
PAGE
張數 1 OF 1

PART NO.
料號 W9115-XXPATBCFR

DATE 制表日
2020/09/23

REV.
版次 B